


# Solid prefinished parquet

speed of installation  
simplicity of installation  
lifespan / durability  
attractive prices  
under floor heating  
product range  
possibility of refinishing  
warmth / character



**Solid parquet has all advantages of wooden flooring.** Wood is one of the oldest and most appreciated material, used for the flooring. It has distinctive, unique natural structure and colour. Solid parquet is an investment for several generations. Its thickness allows it to be renewed (sanded) several times. Boards are of different dimensions. Lengths range from 400 mm to 1500 mm, widths from 82 mm to 120 mm and thicknesses from 18 mm to 20 mm. Solid parquet has to be fully glued to the surface. All parquets are already sanded and varnished or oiled. Some of them have also additional treatments, such as brushing, handscraping, etc. Varnishes and oils are hardened with UV rays. The bevelled edges of the planks additionally emphasize distinctive wood structure.

#### Tehnickal data:

plank dimension	different
underfloor heating	unsuitable
installation	fully glued on the surface
durability	renewable

#### Tongue+groove system





## SOLID PREFINISHED PARQUET - OAK



**OAK AB**



**OAK ABCD**



**OAK ABCD, LIGHT SMOKED, OIL**



**OAK BRUSHED, BLACK EDGES AND PORE**



**OAK BRUSHED, 002**



**OAK BRUSHED, 003 COGNAC**



**OAK ABC BRUSHED, WHITE WASHED, STIL 1**



**OAK AB, BRUSHED, WHITE WASHED, STIL 2**



**OAK ABCD, HAND SCRAPED, WHITE**



**OAK ABCD, CRIMSON**




**OAK ABCD, HAND SCRAPED, 031**



**OAK ABCD, HAND SCRAPED, COFFE**

Tongue+groove



DL x 83/90/125/150/190 x 18/20 mm



## SOLID PREFINISHED PARQUET - of exotic timbers

There is large number of exotic timbers in our solid wood flooring assortment and includes African, Asian and South American wood species. The majority of these wood species is characterized by a high degree of stability, which is especially important for solid wood floorings.



**JATOBA**



**IPE**



**PILANG**



**MERBAU**



**PYNKADO**



**TIGERWOOD**



**TEAK**



**KEMPAS**



**CUMARU**



**BLACK SIRIS**



**ZEBRANO**



**ASH**



**BLACK BIRCH**



**CHESTNUT**




**DOUSSIE**



**PALISANDER**

Tongue+groove




DL x 90/91/92/93/120/124 x 15/18 mm



**IROKO**



**ACACIA NATURAL**



**ASH TERMO WHITE WASHED**



**MAPLE CANADIAN**



**KUKU**



**ASH TIGER**



**AMERICAN WALNUT**



**AMERICAN CHERRY**



**BAMBOO HORIZONTAL,  
MAT WHITE**



**BAMBOO HORIZONTAL TEAK,  
LACQUERED**



**BAMBOO VERTICAL DARK,  
LACQUERED - UNLACQUERED**




**BAMBOO HORIZONTAL DARK,  
LACQUERED - UNLACQUERED**



**BAMBOO VERTICAL,  
LACQUERED - UNLACQUERED**




**BAMBOO HORIZONTAL,  
LACQUERED - UNLACQUERED**



**TEAK MARIN AB**

- speed of installation
- simplicity of installation
- lifespan / durability
- attractive prices
- under floor heating
- product range
- possibility of refinishing
- warmth / character



## SOLID PARQUETS - unfinished

**...shows off the original colour and texture of wood.** The parquet surface is sanded but not additionally treated and the same lengths are available as with solid prefinished parquet. It has to be fully glued to the surface. Final treatment is a matter of taste and requirements. The parquet's thickness allows it to be sanded many times, which proves an important feature especially in more heavily used spaces. In most cases the parquet blocks have straight rather than angled edges.



**AFROMOSIA**



**BUBINGA**



**CUMARU**



**DOUSSIE**



**GARAPA**



**LAPACHO**



**IROKO**



**JATOBA**



**ASH ESPRESSO**



**ASH TIGER**



**TIGERWOOD**



**SYCAMORE**



**SUCUPIRA**



**TATAJUBA**




**TAURARI**




**WENGE**

Tongue+groove



400-1200 x 80/100x 14/15 mm

speed of installation  
 simplicity of installation  
 lifespan / durability  
 attractive prices  
 under floor heating  
 product range  
 possibility of refinishing  
 warmth / character



## SOLID PARQUETS - industrial floorings

**...use raw parquet and, thanks to their special “techno” look.** They are composed of small lamellas, 6-10 mm wide, 10-20 mm thick and 200-400 mm long. Their constructional properties make them suitable for heavily used spaces. Due to its narrow width, each lamella may be of a slightly different colour, testifying to the wood's natural richness of texture. Lamellas can be laid either parallel or randomly. The light and dark tones mix together in a colourful mosaic, bringing elegance to offices and cosiness to living rooms. After sanding, parquet can be varnished or oiled.



**ZEBRANO**



**DOUSSIE**



**WENGE**



**ACACIA STAMED**



**BIRCH HONEY**



**SONOKELLING**



**ASH ESPRESSO**



**ASH TIGER**



**KEMPAS**



**MERBAU**



**TEAK**



**OAK**



Straight joint



160-420 x 210-360x 14-23 mm