PARQUET OIL REFRESH
NEUTRAL

TECHNICAL DATA SHEET

MAINTENANCE OIL FOR OILED PARQUETS

Ready to use blend of natural oils and hard waxes for an easy and fast maintenance of any oil treated surface in interior. Suitable when the wooden floors are locally dull and worn.
Parquet Oil Refresh Netral is not suitable on white or invisible oiled floors and similar.



Technical data at (20°C – 60% R.H.)	
Appearance	Light brown oil liquid
Density	0,9 kg/L
Ready for traffic	12 - 16 h
Polishing	Next day
Indicative yield	35 – 40 m²/litre
Application temperature	> + 10°C
Cleaning tools	Diluente RMD/91
Storage	12 months in original packaging at ambient T
Packaging	1 litre cans



Instructions for use:
Before applying maintanance oil clean the floor with Parquet Oil Cleaner to remove dirt and grease. Let the floor dry. Stir before use then apply a thin coat of Parquet Oil Refresh with a cloth. Within 15 – 20 minutes spread the product in an uniform way with a polishing machine with a soft pad. To get a brighter aspect, the day after polish with a soft cloth or a polishing machine.
After the treatment with PARQUET OIL REFRESH NEUTRAL, wait for 2 weeks before the first washing with PARQUET OIL CLEANER. For periodical maintenance, the application of PARQUET POLISHER is recommended.

Notes:
- Stir well before use
- Do not apply Parquet Oil Refresh Neutral on old varnishes
- Ventilate the room while oiling
- Drying times can be affected by ambient conditions like high R.H. or low temperatures: in this case the drying is slower

Safety regulations:
The product is intended for professional use. Strictly follow the instructions on the label and review the safety data sheet before use.
N.B.: CLOTHS AND SPONGES SOAKED OF PRODUCT MIGHT TO CATCH FIRE THROUGH AUTO-COMBUSTION. AFTER USE WET THEM WITH A LOT OF WATER, LET THEM DRYING AND DISPOSE THEM IN ACCORDANCE OF LOCAL FORCE REGULATION.

Waste disposal:
Dispose of unused product and empty packaging in accordance with applicable local legislation.

Supplier:	Alpod d.o.o., Slovenia
Product code:	FLECAR-OIL010
EAN code:	3830044749002

WARNING: All information provided in this technical data sheet is for informational purposes only and does not constitute a binding obligation. Please take into account environmental conditions and the materials to be treated when using our products. Rev. 04 – 21 June 2024 – This technical data sheet replaces the previous version.